


32A 3P (2P+E) 6H

32A 3P IP44 CEE 90° Angled Wall-Mounted Inlet (with Spring Lid)

PRODUCT CODE BC1-3403-2235



TECHNICAL DRAWING



RATED CURRENT

32A 3P

RATED VOLTAGE

220V-250V

POLES

2P+E

FREQUENCY

50Hz - 60Hz

IP RATING

IP44

HOUSING MATERIAL

Polyamide 6

QUALITY CERTIFICATES



PRODUCT DESCRIPTION

Bemis 32A 3P IP44 CEE 90° Angled Wall-Mounted Inlet (with Spring Lid) (BC1-3403-2235) is a CEE (IEC 60309 type) wall-mounted inlet used to take supply at a fixed surface point. With 32A rated current and 2 poles + earth (3-pin) contact arrangement, it is rated 220V-250V / 50Hz - 60Hz for single-phase systems. IP44 protects against solid objects larger than 1 mm and against water splashing from any direction. Housing material is Polyamide 6 and contacts are MS 58 (brass). The 6h clock position shows where the earth contact sits relative to the keyway and prevents plugs and sockets of different voltage or frequency systems from mating.

TECHNICAL SPECIFICATIONS

ELECTRICAL DATA

Rated Current	32A 3P
Rated Voltage	220V-250V
Poles	2P+E
Frequency	50Hz - 60Hz

MECHANICAL & MATERIAL

IP Rating	IP44
-----------	-------------

Housing Material **Polyamide 6**Contact Material **MS 58 (brass)**

PACKAGING & LOGISTICS

Pieces Per Box	3
Pieces Per Carton	36
Weight (g)	292,7 g

GENERAL

Clock Position **6h**