


32A 4P (3P+E) 6H

32A 4P IP67 CEE Connector

PRODUCT CODE BC1-3504-7312



TECHNICAL DRAWING



RATED CURRENT

32A 4P

RATED VOLTAGE

380V-450V

POLES

3P+E

FREQUENCY

50Hz - 60Hz

IP RATING

IP67HOUSING
MATERIAL**Polyamide 6**

QUALITY CERTIFICATES



PRODUCT DESCRIPTION

Bemis 32A 4P IP67 CEE Connector (BC1-3504-7312) is a CEE (IEC 60309 type) connector (portable socket-outlet) fitted to the end of a flexible cable to create a mobile power point. With 32A rated current and 3 phases + earth (4-pin) contact arrangement, it is rated 380V-450V / 50Hz - 60Hz for three-phase systems. IP67 is fully dust-tight and withstands temporary immersion in water. Housing material is Polyamide 6 and contacts are MS 58 (brass). The 6h clock position shows where the earth contact sits relative to the keyway and prevents plugs and sockets of different voltage or frequency systems from mating.

TECHNICAL SPECIFICATIONS

ELECTRICAL DATA

Rated Current	32A 4P
Rated Voltage	380V-450V
Poles	3P+E
Frequency	50Hz - 60Hz

MECHANICAL & MATERIAL

IP Rating	IP67
-----------	------

Housing Material **Polyamide 6**Contact Material **MS 58 (brass)**

PACKAGING & LOGISTICS

Pieces Per Box	3
Pieces Per Carton	36
Weight (g)	311,1 g

GENERAL

Clock Position	6h
----------------	----