


63A 3P (2P+E) 6H

63A 3P IP67 CEE 90° Angled 16A. Wall-Mounted Inlet with Panel Socket

PRODUCT CODE BC1-4403-7238



TECHNICAL DRAWING



RATED CURRENT

63A 3P

RATED VOLTAGE

220V-250V

POLES

2P+E

FREQUENCY

50Hz - 60Hz

IP RATING

IP67

HOUSING MATERIAL

Polyamide 6

QUALITY CERTIFICATES



PRODUCT DESCRIPTION

Bemis 63A 3P IP67 CEE 90° Angled 16A. Wall-Mounted Inlet with Panel Socket (BC1-4403-7238) is a CEE (IEC 60309 type) wall-mounted inlet used to take supply at a fixed surface point. With 63A rated current and 2 poles + earth (3-pin) contact arrangement, it is rated 220V-250V / 50Hz - 60Hz for single-phase systems. IP67 is fully dust-tight and withstands temporary immersion in water. Housing material is Polyamide 6 and contacts are MS 58 (brass). The 6h clock position shows where the earth contact sits relative to the keyway and prevents plugs and sockets of different voltage or frequency systems from mating.

TECHNICAL SPECIFICATIONS

ELECTRICAL DATA

Rated Current	63A 3P
Rated Voltage	220V-250V
Poles	2P+E
Frequency	50Hz - 60Hz

MECHANICAL & MATERIAL

IP Rating	IP67
-----------	-------------

Housing Material **Polyamide 6**Contact Material **MS 58 (brass)**

PACKAGING & LOGISTICS

Pieces Per Box	1
Pieces Per Carton	7
Weight (g)	1016 g

GENERAL

Clock Position	6h
----------------	-----------