

DC FAST CHARGERS

40kW DC Fast Charging Station · Wall-mounted

PRODUCT CODE BEVDCC-4223-0005



TECHNICAL DRAWING

40 kW Wall Mounted




Dimensions (mm)

Width (W) : 600
Depth (D) : 320
Height (H) : 900

Weight (kg)

40 kW : 80

40 kW Pedestal Type (optional)



Dimensions (mm)

Width (W) : 600
Depth (D) : 425
Height (H) : 1770

Weight (kg)

40 kW : 105

QUALITY CERTIFICATES



PRODUCT DESCRIPTION

BEVDC 40 – 40kW DC Fast Charging Station · Wall-mounted (BEVDCC-4223-0005) is a DC fast charger designed for public stations, fleets and commercial sites. Key specifications: Connector: CCS2; IP Rating: IP54; Output Power: 40 kW; Introduction: AC 380-480V, 3 Phase. Highlights: OCPP, RFID Card Reader, Shared Access, CCS2, LCD Display. It is used at motorway service areas, shopping centres, car park operators and fleet depots; project-based site surveys and commissioning support are available. You can download the datasheet on this page and request a quote direct from the manufacturer with your quantities and project details.

TECHNICAL SPECIFICATIONS

ELECTRICAL DATA		Input	AC 380-480V, 3 Phase
Frequency	50/60 Hz	Number of Sockets	1
Output Power	40 kW	Concurrent	No
Output Voltage	150-1000V DC	User Authentication	RFID Card + Mobile App
MECHANICAL & MATERIAL		Connectivity	Ethernet / 4G
IP Rating	IP54	Payment Methods	RFID / NFC contactless, Credit/Debit Card (CPO), Mobile
Dimensions (W×D×H)	600 × 320 × 900 mm	Installation	Outdoor
Weight	80 kg	Warranty	2-year manufacturer (optional +3-year extension for a fee)
GENERAL		Domestic Goods Certificate	%94
Connector	CCS2	Certification	CE
Protocol	OCPP 1.6J / 2.0.1		
Operating temperature:	-25°C ~ +55°C		