

EV CHARGER COMPONENTS

Open-Ended Power Cable – 32A 5P · Three-phase 22 kW · 5×6 mm²

PRODUCT CODE **BKT-1000-2700**

POWER

22 kW

PHASE

Three-phase

CABLE LENGTH

1,5m

PLUG

32A 5P Plug

CABLE SECTION

5 × 6 mm² ttr

OTHER END

ON (for OEM integration)

QUALITY CERTIFICATES



PRODUCT DESCRIPTION

Open-Ended Power Cable – 32A 5P · Three-phase 22 kW · 5×6 mm² (BKT-1000-2700) is a charger component developed for charging station manufacturers and integrators. Key specifications: Power: 22 kW; Phase: Three-phase; Cable Length: 1,5m; Cable section: 5 × 6 mm² ttr. Highlights: Three-phase 22 kW power input, CE conformity testing completed. It is used as an OEM component in the production and maintenance of AC and DC chargers; quotes are available for series supply and custom lengths. You can download the datasheet on this page and request a quote direct from the manufacturer with your quantities and project details.

TECHNICAL SPECIFICATIONS

ELECTRICAL DATA		GENERAL	
Power	22 kW	Plug	32A 5P Plug
Phase	Three-phase	Cable section	5 × 6 mm ² ttr
Cable Length	1,5m	Other End	ON (for OEM integration)